

Super Hauler Gas Specifications

DIMENSIONS

OVERALL LENGTH	143.0 in (3,632 mm)
OVERALL WIDTH	53.0 in (1,346 mm)
OVERALL HEIGHT (w suntop)	71.9 in (1,826 mm)
WHEELBASE	98.1 in (2,492 mm)
FRONT WHEEL TREAD	34.3 in (870 mm)
REAR WHEEL TREAD	38.6 in. (980 mm)
MINIMUM GROUND CLEARANCE	4.5 in (114 mm)

ENGINE/DRIVE TRAIN

ENGINE TYPE	Yamaha built, low emission single cylinder 60° incline OHV
DISPLACEMENT	357 cc
BORE x STROKE	85 x 63 mm
HORSEPOWER	11.4 HP (8.5 Kw/3500 rpm)
COMPRESSION RATIO	8.1:1
LUBRICATION SYSTEM	Splash style positive oil lubrication
OIL CAPACITY	1 U.S. quart (1 liter, 1000 cc)
AIR CLEANER	Two stage, urethane-foam pre-cleaner and high-capacity pleated paper cartridge
COOLING SYSTEM	Forced air
CARBURETOR	Mikuni BV26-18
IGNITION SYSTEM	Transistor magneto ignition
TRANAXLE	EnduraDrive™ V-belt automatic forward/reverse transaxle equipped with high-precision helical gears, 11.40:1 drive axle ratio

CHASSIS

FRAME	HybriCore™ Chassis features a robotic welded automotive ladder-style steel frame mated to a polypropylene structural floor. Frame is protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and a electrostatic applied polyester/urethane powder topcoat
BODY	FRONT:Custom-formulated thermoplastic olefin; front is painted with a two-part topcoat of high-luster automotive grade polyurethane REAR: Powder Coated Aluminum
STEERING	Self-compensating double reduction helical rack-and-pinion, permanently lubricated with sealed bearings and greaseless tie-rod ends
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers
BRAKES	Maintenance-free internal transaxle disc brake
SEATING	Seamless, fabric-backed vinyl bonded to pure, virgin foam contoured seat cushions and mated to a warp and moisture resistant polypropylene bottom, strengthened with plated steel inserts
BUMPER	Front 5 mph energy-absorbing bumper

PERFORMANCE

MAX FORWARD SPEED	15 mph (24 km/h)
MAX REVERSE SPEED	11.4 mph (18.4 km/h)
TURNING RADIUS	13.5 ft (3.4 m)

GENERAL

DRY WEIGHT	893 lbs (405 kg)
CARGO BOX MATERIAL	Aluminum with Powder Coated Aluminum Rails
CARGO BED CAPACITY	800 lbs (363 kg)
CARGO BED SIZE (LxWxH)	72.0 in (1,829 mm) x 48.0 in (1,219 mm) x 7.0 in (178 mm)
FUEL TANK CAPACITY	5.8 US gal (22.0 L)
TIRE SIZE	18.00 x 8.50-8.00 (6-ply rating)
SEATING CAPACITY	2 persons
AVAILABLE PAINT COLORS	Glacier
AVAILABLE TOP COLORS	Black
AVAILABLE SEAT COLOR	STANDARD: Black OPTIONAL: Stone

WARRANTY

WARRANTY	Standard 2-year limited vehicle warranty
----------	--